

COR-IP2BVA

2MP STARLIGHT VARIFOCAL NETWORK CAMERA with MOTORIZED ZOOM



KEY FEATURES

- 1/2.8" Progressive CMOS
- 2.8 ~ 13.5 mm (Motorized) IR Lens
- Premium Starlight Technology
- Dragonfire® LEDs
- IR Range up to 145 feet
- Metal Housing IP66 Waterproof
- 1920(H)×1080(V) Resolution



SPECIFICATIONS

Resolution	2MP 1920 (H) × 1080 (V)
Image Sensor	1/2.8" Progressive CMOS
Min.Illumination	Color 0.01lux @ F1.2 (AGC ON) ; B/W 0 lux @ IR ON
Shutter Time	Auto/Manual 1/5 ~ 1/20000s
Slow Shutter	Support
Lens	2.7 ~ 13.5 mm (Motorized) H.FOV: 111 ~ 33°
F-No	F No. 1.83 (W) ~ 3.32 (T) ±5%
Day & Night	IR cut filter with auto switch (Day / Night / Auto / Schedule)
DNR	3D DNR
WDR	120 dB
Video Compression	H.265 / H.264
Video Bit Rate	8Kbps ~ 8Mbps
Triple Stream	Yes
Resolution	Mainstream (default 30fps) 1080P (1920x1080), 720P (1280x720), Substream (default 10fps) 720P (1280x720),VGA (640x480), QVGA (320x240) Mobilestream (default 10fps) VGA (640x480), QVGA (320x240)
Image Settings	Flip,Rotation,Corridor mode, Saturation, Hue, Brightness, Contrast, Sharpness adjustable
BLC	Support
ROI	Support
Privacy Mask	Support

Smart Feature	Face Detection, Human / Vehicle Detection
AI Analytics	Cross line Detection, Intrusion Detection, Stationary Object Alert
Protocols	TCP / IP, HTTP, DHCP, DNS, DDNS, RTP / RTSP, PPPoE, SMTP,NTP, UPnP, SNMP, HTTPS, FTP,
System Compatibility	Open Compatibility, (Profile S, G, T)
Network Interface	RJ45 10M / 100M Ethernet interface x1
LED	4 pcs (Array) (DragonFire® SMD)
IR Range	Up to 145 feet (45m)
ePTZ	Digital Pan Tilt Zoom
SD Storage	Yes (Micro SD / SDHC / SDXC slot, up to 128 GB)
Alarm Trigger	1 input / 1 output
Audio	1 input / 1 output (RCA)
Video Output	NA
Reset System	Yes
PoE	Yes
Waterproof	Metal Housing IP66
Input Voltage / Current	DC 12V / POE
Power Consumption	4.8W
Storage Conditions	-30~+60°C (-22~+140°F) / less than ≤ 95% RH
Operating Conditions	-30~+55°C (-22~+131°F)
Dimensions	265 x 120 x 115 mm (10.4 x 4.72 x 4.5 inches)
Weight	Approximately 1.77 lbs (806g)

COR-IP2BVA

